



HQ 103 HFFR A

ÖREN HQ 103 HFFR A

Class A

RoHS Compliant CE CPR COMPLIANT

Käyttö

Tämä RG6 kaapeli on suunniteltu erityisesti käytettäväksi multimediaverkoissa ja se täyttää kaapeliverkko-operaattoreiden edellyttämän A luokan suojausvaatimuksen. Pitkäikäisen kaapelin ominaisuuksia ovat mm. pieni vaimennus sekä suuri suojausvaimennus.

Kaapelin Rakenne

Sisäjohdin
Ø 1.02 mm Puhdas kupari

Eristys
Ø 4.80 mm Gas Injected Skin/Foam/Skin PE

1. Ulkojohdin
Alumiinifolio
liimattu eristeeseen

2. Ulkojohdin
Alumiinilankapunos
54% Punospeitto

3. Ulkojohdin
Alumiinifolio
Liimattu ulkoeristeeseen

Ulkosuojaus
Ø 6.80 mm HFFR*

Kelakoko / Sähkönumero

250 m / 02 323 48
500 m / 02 323 49

Mekaaniset ominaisuudet

Kaapelin paino	45 kg/km
Kuparin paino	7.8 kg/km
Min. taivutussäde	35 mm
Maks. vetolujuus	110 N
Käyttölämpötila	-30 °C ... +70 °C
Pakkaus	250 / 500 m

Sähköiset ominaisuudet

Impedanssi	75 ± 2 Ω
Kapasitanssi	53 ± 2 pF/m
Nopeuskerroin	% 84
Eristysvastus	> 2 GΩxkm
Käyttöjännite	1300 V
Koestusjännite	3000 V
Sisäjohtimen DCR	< 22.10 Ω/km

Vaimennus (20°C)

5 MHz	1.50 dB/100m
50 MHz	4.40 dB/100m
230 MHz	9.00 dB/100m
470 MHz	14.00 dB/100m
862 MHz	19.29 dB/100m
1000 MHz	20.91 dB/100m
1750 MHz	28.37 dB/100m
2150 MHz	31.80 dB/100m
2400 MHz	33.76 dB/100m
3000 MHz	38.17 dB/100m

Heijastusvaimennus (20°C)

5-470 MHz	> 30 dB
470-1200 MHz	> 25 dB
1200-2000 MHz	> 23 dB
2000-3000 MHz	> 18 dB

Kytkentäimpedanssi

5-30 MHz	< 5 mΩ/m

Suojausvaimennus

30-1200 MHz	> 100 dB
1200-2000 MHz	> 95 dB
2000-3000 MHz	> 90 dB

Standardit

Suojausluokka Class A
EN 50117-9-2

Euro luokka
C_{ca} , s1, d1, a1

Palamisnopeus
EN 60332-1-2

Syövyttävien kaasujen testaus
EN 50267-2-3

Savunmuodostus
EN 61034-2

Application

This RG6 type cable is specifically designed for use in multimedia networks and complies with screening of class A level. It has characteristics such as low loss, high screening efficiency, and high resistance to aging.

Cable Construction

Inner Conductor
Ø 1.02 mm Bare Copper

Insulation
Ø 4.80 mm Gas Injected Skin/Foam/Skin PE

1st Shielding
Aluminum Foil
Bonded to the Insulation

2nd Shielding
Aluminum Wire Braiding
54% Covarage

3rd Shielding
Aluminum Foil
Bonded to the Outer Sheath

Outer Sheath
Ø 6.80 mm HFFR*

Reel Size / Number

250 m / 02 323 48
500 m / 02 323 49

Technical Properties

Cable Weight	45 kg/km
Copper Weight	7.8 kg/km
Min. Bending Radius	35 mm
Max. Tensile Strength	110 N
Temperature Range	-30 °C ... +70 °C
Packing	250 / 500 m

Electrical Properties

Impedance	75 ± 2 Ω
Capacitance	53 ± 2 pF/m
Velocity of Propagation	84 %
Insulation Resistance	> 2 GΩxkm
Operating Voltage	1300 V
Test Voltage	3000 V
Inner Conductor DCR	< 22.10 Ω/km

Attenuations (20°C)

5 MHz	1.50 dB/100m
50 MHz	4.40 dB/100m
230 MHz	9.00 dB/100m
470 MHz	14.00 dB/100m
862 MHz	19.29 dB/100m
1000 MHz	20.91 dB/100m
1750 MHz	28.37 dB/100m
2150 MHz	31.80 dB/100m
2400 MHz	33.76 dB/100m
3000 MHz	38.17 dB/100m

Return Loss (20°C)

5-470 MHz	> 30 dB
470-1200 MHz	> 25 dB
1200-2000 MHz	> 23 dB
2000-3000 MHz	> 18 dB

Transfer Impedance

5-30 MHz	< 5 mΩ/m

Screening Attenuation

30-1200 MHz	> 100 dB
1200-2000 MHz	> 95 dB
2000-3000 MHz	> 90 dB

Standards

Screening Class Class A
EN 50117-9-2

Euro Class
C_{ca} , s1, d1, a1

Flame Retardancy
EN 60332-1-2

Corrosive Gases Test
EN 50267-2-3

Smoke Density
EN 61034-2

* HFFR (Halogen Free, Flame Retardant) = FRNC (Flame Retardant, None Corrosive) = LSNH (Low Smoke None Halogen) = LSZH (Low Smoke Zero Halogen) = LS0H (Low Smoke Zero Halogen)